

**REVERSIBLE THERMOSENSITIVE RECORDING MEDIUM**

**Publication number:** JP2188293

**Publication date:** 1990-07-24

**Inventor:** WATANABE JIRO; SHIMIZU TOYOKO; HINO YOSHIHIRO

**Applicant:** TOPPAN PRINTING CO LTD

**Classification:**

- international: **B41M5/26; B41M5/30; B41M5/26; B41M5/30; (IPC1-7): B41M5/26; B41M5/30**

- european:

**Application number:** JP19890009058 19890118

**Priority number(s):** JP19890009058 19890118

**Report a data error here**

**Abstract of JP2188293**

**PURPOSE:**To chemically develop or discharge a color only by controlling thermal energy by providing a color developer/subtractor which is the salts of bis(hydroxyphenyl) acetic acid or bis(hydroxyphenyl) butyric acid and higher aliphatic amine. **CONSTITUTION:**A recording medium consists of a recording layer containing a leuco compound, a color developer/subtractor which develops or subtracts a color due to thermal reaction with the leuco compound and a binder as main components, provided on a support. The color developer/subtractor is the salts of bis(hydroxyphenyl) acetic acid or bis(hydroxyphenyl) acetic acid and higher aliphatic amine. More clearly, coating liquid for a recording layer is obtained by dissolving the binder in a coating liquid prepared by dispersing or dissolving dye in water or an organic solvent, and adding thickener or white pigment as liquid quality improver. This coating liquid is applied to a support such as paper, plastic film or sheet, and then is dried to form a recording layer.

---

Data supplied from the **esp@cenet** database - Worldwide